

NAT'L INST. OF STAND & TECH R.I.C.



A11105 142027

NIST  
PUBLICATIONS

**ANSI/NIST-ITL 1a-1997  
Addendum To  
ANSI/NIST-CSL 1-1993**

**and  
NISTIR 6011**

**American National Standard  
For Information Systems—**

# **Data Format for the Interchange of Fingerprint, Facial & SMT Information**

QC  
100  
.U56  
NO.6011  
1997

**United States Department of Commerce  
Technology Administration  
National Institute of Standards and Technology**

**NIST**



**ANSI/NIST-ITL 1a-1997  
and  
NISTIR 6011**

**Addendum To  
ANSI/NIST-CSL 1-1993**

**American National Standard  
For Information Systems—**

# **Data Format for the Interchange of Fingerprint, Facial & SMT Information**

**Sponsor  
National Institute of Standards and Technology**

**Approved April 7, 1997  
American National Standards Institute, Inc.**

Issued April 1997



**U.S. Department of Commerce**  
William M. Daley, Secretary  
**Technology Administration**  
Mary L. Good, Under Secretary for Technology  
**National Institute of Standards and Technology**  
Robert E. Hebner, Acting Director

This document is a contribution of the National Institute of Standards and Technology and is not subject to copyright. Any organization interested in reproducing ANSI/NIST-ITL 1a-1997, *Data Format for the Interchange of Fingerprint, Facial & SMT Information* is free to do so. However, there shall be no alteration to any of the material contained in the document.

# CONTENTS

FOREWORD .....	V
0 INTRODUCTION .....	1
1 SCOPE, PURPOSE, AND APPLICATION .....	1
1.1 SCOPE .....	1
1.2 PURPOSE .....	1
1.3 APPLICATION .....	1
2 NORMATIVE REFERENCES .....	2
3 DEFINITIONS .....	2
3.1 - 3.8 REFER TO ANSI/NIST-CSL 1-1993 .....	2
3.9 RGB .....	2
3.10 SMT .....	2
3.11 ASPECT RATIO .....	2
3.12 MUGSHOT .....	2
4 TRANSMITTED DATA CONVENTIONS .....	2
4.1 - 4.3 REFER TO ANSI/NIST-CSL 1-1993 .....	2
4.4 SCAN SEQUENCE .....	2
4.5 COLOR DATA .....	2
5 IMAGE RESOLUTION REQUIREMENTS .....	3
6 FILE DESCRIPTION .....	3
6.1 FILE FORMAT .....	3
6.2 FILE CONTENTS .....	3
6.3 IMAGE DESIGNATION CHARACTER (IDC) .....	3
7 RECORD DESCRIPTION .....	4
7.1 LOGICAL RECORD TYPES .....	4
7.2 RECORD FORMAT .....	4
8 TYPE-1 TRANSACTION RECORD .....	5
9 - 17 Refer to ANSI/NIST-CSL 1-1993 .....	5
18 TYPE-10 FACIAL & SMT IMAGE RECORD .....	5
18.1 FIELDS FOR TYPE-10 LOGICAL RECORD .....	5
18.2 END OF TYPE-10 LOGICAL RECORD .....	13
18.3 ADDITIONAL FACIAL & SMT IMAGE RECORDS .....	13
ANNEX E .....	15
ANNEX F .....	23

# TABLES

Table 8: Logical Record Type (Additional) .....	3
Table 9 Number of Logical Records Per Transaction (Additional).....	4
Table 10 Type-10 Logical Record Layout.....	6
Table 11 - Subject Pose.....	9
Table 12 - Photo Descriptors.....	9
Table 13 Tattoo Classes .....	10
Table 14a Human Tattoo Subclasses.....	11
Table 14c Plant Tattoo Subclasses.....	11
Table 14b Animal Tattoo Subclasses .....	11
Table 14d Flags Tattoo Subclasses .....	11
Table 14e Objects Tattoo Subclasses .....	12
Table 14g Symbols Tattoo Subclasses .....	12
Table 14f Abstract Tattoo Subclasses .....	12
Table 14h Other Tattoo Subclasses .....	12
Table 15 Color Codes .....	13

## **Foreword** (This foreword is not part of the American National Standard ANSI/NIST-ITL 1a-1997.)

Federal, state and local law enforcement and related criminal justice agencies have procured or are in the process of procuring electronic image capture, storage, and retrieval systems intended to facilitate the determination of the personal identity of a subject. This equipment will be used to capture a subject's mugshot (or facial image), and any scars, marks, or tattoos (SMT) present on the subject's body.

Digital cameras and other type of video recorders capture images and produce digital image files directly from the subject's head and body. Scanners are used to digitize images from photographs, pictures, or sketches. The digital representations of these image files consist of grayscale or color pixels depending on the application and equipment.

These digital images are stored in a compressed or uncompressed form in an image storage and retrieval system (ISR). Textual descriptive data and other information for each image is also stored. When required, specific images from a master file can be retrieved from the ISR and be incorporated as part of an electronic mugshot book, or an electronic line-up. Images selected may be the result of textual filters based on physical descriptive or information fields indexed to each image. Stored SMT images can also be retrieved as part of an identification process. The actual identification are made by a human witness or an examiner using images retrieved from the system.

To effectively exchange mugshot and SMT identification data across jurisdictional lines or between dissimilar systems produced by different manufacturers, a standard is needed to specify the content and common format for the data exchange. The data may be images captured from digital cameras or the digital representation of scanned photographs or pictures.

The Information Technology Laboratory (ITL), previously the Computer Systems Laboratory, of the National Institute of Standards and Technology (NIST) sponsored the development of the addendum to the Data Format for the Interchange of Fingerprint Information (ANSI/NIST-CSL 1-1993). This addendum enhances the original standard by specifying the data elements required for the exchange of mugshot and SMT information. Consensus during its development was achieved through the use of the Canvass Method.

The sections of this document are numbered in accordance with the corresponding sections in the ANSI/NIST-CSL 1-1993 standard. Section numbers matching those in the standard provide additional information. Section numbers appearing in this addendum, but not in the original standard, provide information that describes the format for the two additional types of image data. Sections appearing in the original standard, but not in this addendum, imply that no additional details are required to accommodate the new image types.

This addendum contains two annexes. Annex E, a description of the Joint Photographic Experts Group (JPEG) File Interchange format, is normative and considered part of the addendum. Annex F, contains examples of facial and tattoo images formatted in accordance with this addendum. It is informative and not considered as part of the addendum.

Suggestions for the improvement of this standard will be welcome. They should be sent to the attention of R.M. McCabe, Mugshot Standards, Visual Image Processing Group, NIST, Building 225, Room A-216, Gaithersburg, MD 20899.

The following organizations recognized as having an interest in the standardization of the data format for the interchange of mugshot and SMT information were contacted prior to the approval of this addendum to the standard. Inclusion in this list does not necessarily imply that the organization concurred with the submittal of the proposed standard to ANSI.

Abilene Police Department  
Bureau of Alcohol, Tobacco and Firearms  
Chicago Police Department  
Cogent Systems Inc.  
D.C. Metropolitan Police Department  
Information Services Division  
Data Critical Corporation  
Detroit Police - Identification Unit  
Digital Biometrics, Inc.  
Digital Descriptor Systems Inc.  
Digital Facial Identification System  
Eastman Kodak Co.  
ECG Management Consultants  
Elk Grove Village Police Department  
EPIC Solutions, Inc.  
Federal Bureau of Investigation - CJIS  
Federal Bureau of Investigation - Photography  
Laboratory  
Fingermatrix, Inc.  
Fingerprint USA  
Florida Department of Law Enforcement  
Georgia Bureau of Investigation  
Gregg Thompson Associates  
Higgins & Associates, International  
IDENTIX, Inc.  
Illinois State Police  
Indianapolis Police Department  
Infotec Development, Inc.  
King County Police  
LA County Sheriff Department  
Las Vegas Metropolitan Police  
Lockheed Martin Energy Systems  
Manchester, MO Police Department  
Massachusetts State Police  
MD Department of Public Safety & Correctional  
Services

MD State Police - Crime Laboratory  
Metropolitan Police Service, London, England  
Michigan State Police - AFIS  
Missouri State Highway Patrol  
Mitretek Systems, Inc.  
National Institute of Justice  
North American Morpho Systems, Inc.  
NY State Division Criminal Justice Services  
Peel Regional Police  
Philadelphia Police Department  
Positive Identification, Inc.  
PRC  
PRINTRAK International, Inc.  
R.T. Moore Associates  
River City Research Group  
Riverside County Sheriff  
Robert Stock Associates  
Royal Canadian Mounted Police  
San Antonio, TX Police Department  
Saber Imaging  
San Jose State University  
Sayers Advanced Systems  
Search  
Sirchie Finger Print Labs  
State of Connecticut Department of Public Safety  
Tacoma, WA Police Department  
Texas Department of Public Safety  
TFP Inc.  
TRW SIG  
UNISYS Corp.  
Virginia State Police  
Visible Edge, Inc.  
Vision Control Int. Pty. Lt.  
VT Department of Public Safety  
Western Identification Network (WIN)  
XImage Corporation

# Data Format for the Interchange of Fingerprint, Facial & SMT Information (ANSI/NIST-ITL 1a-1997)

## 0 Introduction

In 1993, ANSI approval was obtained for the "Data Format for the Interchange of Fingerprint Information" standard (ANSI/NIST-CSL 1-1993). The standard specifies formats to be used for exchanging fingerprint and signature image data. Provisions are also included for the exchange of textual or ASCII data describing a subject's demographic characteristics and a limited amount of minutiae or fingerprint characteristic data. The data to be exchanged are contained in nine defined record types and formatted according to specific requirements.

As a result of agreements reached at the Mugshot and Facial Image Workshop held in Gaithersburg on October 23-25, 1995, the standard has been expanded to address two additional types of biometric image data. This expansion of the standard is in the form of an addendum that specifies a record structure capable of handling the exchange of both types of images.

The first type consists of facial image or mugshot data. The second type pertains to scar, mark, and tattoo (SMT) image data. A provision has also been introduced to enable the exchange of non-specific, user-definable type images that do not fall under any of the defined image type.

## 1 Scope, purpose, and

## application

### 1.1 Scope

This addendum defines the content, format, and units of measurement for the exchange of information that may be used in the identification of a subject based on facial/mugshot and/or SMT image information. This data shall consist of a variety of mandatory and optional items, including related descriptive data, scanning parameters, and compressed or uncompressed digitized images. This information is intended for interchange between criminal justice administrations or organizations that use facial/mugshot or SMT data for identification purposes.

### 1.2 Purpose

Information compiled and formatted in accordance with this addendum can be recorded on machine-readable media and may be transmitted over data communications facilities. Law enforcement and criminal justice agencies may use it to exchange facial/mugshot and SMT images and related identification data.

### 1.3 Application

Systems claiming conformance with this addendum shall be capable of

transmitting and receiving Type-1, and Type-10 records and shall specify which other record types are implemented for transmitting, or receiving, or both. Record types not implemented shall be ignored.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard Addendum.

ANSI/NIST-CSL 1-1993, Information systems - Data Format for the Inter-change of Fingerprint Information<sup>1</sup>

ISO International Standard 10918-1, Information Technology - Digital Compression and Coding of Continuous-Tone Still Images Part 1: Requirements and Guidelines<sup>2</sup> (Commonly referred to as the Joint Photographic Experts Group (JPEG) algorithm).

## 3 Definitions

The following definitions and those given in ANSI/IAI 2 and ANSI/NIST-CSL 1-1993 apply to this addendum.

### 3.1 - 3.8 Refer to ANSI/NIST-CSL 1-1993

**3.9 RGB:** Red, Green, Blue. Used to represent color pixels comprised of a specified number of bits to represent each of these primary color components.

**3.10 SMT:** Abbreviation used for scar, mark, and tattoo information.

**3.11 aspect ratio:** The width to height ratio of the captured image.

**3.12 mugshot:** Term used interchangeably with facial image. The term facial image usually implies a higher quality image than a mugshot.

## 4 Transmitted data conventions

### 4.1 - 4.3 Refer to ANSI/NIST-CSL 1-1993

### 4.4 Scan sequence

For each grayscale or color facial or each grayscale or color SMT image that was captured and formatted, the transmitted scan sequence shall be assumed to have been left to right and top to bottom.

For the purpose of describing the position of each pixel within an image, a pair of reference axes shall be used. The origin of the axes, pixel location (0,0), shall be located at the upper left-hand corner of each image. The x-coordinate (horizontal) position shall increase positively from the origin to the right side of the image. The y-coordinate (vertical) position shall increase positively from the origin to the bottom of the image.

### 4.5 Color data

For color facial or SMT images scanned, it shall be assumed that the scanned images consist of nominal 24-bit RGB

<sup>1</sup>Available from the American National Standards Institute, 11 West 42nd Street, New York, NY 10036.

<sup>2</sup>Available from the American National Standards Institute, 11 West 42nd Street, New York, NY 10036.

pixels. For each component of the RGB pixel, its value shall be quantized to eight bits.

Color image data may be transmitted in either compressed or uncompressed form. The transmission of uncompressed color images shall consist of RGB pixels, each of which shall be quantized to 256 levels (8 bits) for each of the three components. For each pixel, the three components shall be sequentially formatted for transmission on a pixel-by-pixel basis. Compressed image data shall adhere to the requirements of the algorithm used.

## 5 Image resolution requirements

For facial and SMT images, the scanner and transmitting resolution requirements are not applicable.

## 6 File description

This addendum describes one additional logical record. It was designed to exchange a combination of ASCII and binary image data within a single logical record structure. At the beginning of the record, a series of tagged fields shall be used to provide information required to process the binary image data present in the last field of the logical record. This logical record type with its identifier is listed in Table 8, Logical Record Type (Additional). This table is an extension of Table 1 in the original standard.

### 6.1 File format

The data fields in the Type-10 record shall be recorded in variable-length fields using the 7-bit American National Standard Code for Information Interchange (ASCII) as described in ANSI

X3.4 and annex A.<sup>3</sup> For each facial and SMT image record that is formulated, the fields contained within that record shall be numerically ordered and their contents shall be as specified in this addendum.

**Table 8: Logical Record Type (Additional)**

Logical record contents	Type identifier
Facial & SMT Image Data	10

This record type shall contain data fields encoded as ASCII textual information. The concluding field of the Type-10 logical record shall have a tagged ASCII identifier followed by the binary image data.

### 6.2 File contents

Table 9, Number of logical records per transaction (Additional), is an extension of Table 2 of the 1993 standard. It lists the number of Type-10 facial and SMT image records that may occur in a transaction file. The appearance of "0-N" in Table 9 indicates that there is no limit on the number of Type-10 logical records that may be contained in the logical file.

### 6.3 Image Designation Character (IDC)

The IDC shall also be used to relate information items in the file contents field of the Type-1 record to each facial or SMT image record. It properly identifies and links together different logical record types created from the same image. As the facial or SMT image can only be represented by the Type-10 logical record, each such image shall have a

<sup>3</sup>This annex can be found in the original standard ANSI/NIST-CSL 1-1993.

**Table 9 Number of Logical Records Per Transaction (Additional)**

Type of Logical Record	Ten-Print Inquiry	Latent Inquiry	File Maintenance	Image Request	Search Response	Image Request Response
10	0-N	0-N	0-N	0-N	0-N	0-N

unique IDC code. The value of the IDC shall be one greater than the last IDC used for the Type-2 through Type-9 logical records in the file. Subsequent IDCs shall be sequentially incremented by one for each new facial or SMT image.

## 7 Record description

### 7.1 Logical record types

#### 7.1.1 - 7.1.9 Refer to ANSI/NIST-CSL 1993

#### 7.1.10 Type-10 facial and SMT image record

Type-10 logical records shall contain, and be used to exchange facial and SMT image data together with textual information pertinent to the digitized image. The source of the image data shall be the image captured from scanning a photograph, or a live image captured with a digital camera.

### 7.2 Record format

#### 7.2.1 Refer to ANSI/NIST-CSL 1-1993

#### 7.2.2 Record layout

The Type-10 record shall use a combination of tagged ASCII field identifiers (as used in the Type-1, Type-2, and Type-9 logical records) followed by ASCII descriptive data for each field. The record shall end with a tagged ASCII

field identifier preceding the binary image data. Each Type-10 record information field that is used, shall be numbered in accordance with this standard. The format of each field shall consist of a field number followed by a colon (:), followed by the information item(s) appropriate to that field. For this logical record, field numbers have the format "10.XXX:", where 10 is the logical record type, and "XXX" is a sequentially assigned field number within that record type. Multiple occurrences of the same subfield within a logical record shall be separated by the *RS* character. Individual information items within a field or subfield shall be separated by the *US* character. In addition to the identifying number, information fields shall be separated from other information fields by the ASCII Group Separator (*GS*) control character.

For each field or subfield that is designated as mandatory, the appropriate information shall be entered in the required format. An optional field shall be omitted when the information for that field is unavailable or unneeded. Each logical Type-10 record shall contain a single image. The last field in the logical record (field 10.999:) shall contain the image data which shall be placed immediately following the colon (":") of the field identifier. The length of the entire record shall be specified by the record length field contained in the record itself. The ASCII File Separator (*FS*) control character shall follow the last byte of the compressed or uncompressed image data. The *FS* character shall signify the end of the logical record.

## **8 Type-1 Transaction record**

### **8.1.1 Refer to ANSI/NIST-CSL 1-1993**

### **8.1.2 Field 1.02: Version Number (VER)**

The entry in this field shall be "0201" to indicate the current version of the standard used to encode the image data. This version number signifies the inclusion of the Type-10 logical record.

### **8.1.3 Field 1.03: File Content (CNT)**

This mandatory field shall list each of the logical records in the logical file by record type. The count of the logical records, which is contained in the second information item of the first subfield, shall include the number of Type-10 records contained in the logical file. A subfield shall be included in Field 1.03 for each Type-10 record present in the logical file. The first information item shall be the two-character code "10" chosen from Table 8, which declares the record type. The second information item shall be the IDC associated with the logical record pertaining to that subfield. The US character shall be used to separate the two information items.

### **8.1.4 - 8.1.10 Refer to ANSI/NIST-CSL 1-1993**

### **8.1.11 Field 1.11: Native Scanning Resolution (NSR)**

This field applies only to fingerprint image data. For those logical files that contain only Type-10 image records, this field shall be set to "00.00".

### **8.1.12 Field 1.12: Nominal Transmitting Resolution (NTR)**

This field applies only to fingerprint image data. For those logical files that contain only Type-10 image records, this field shall be set to "00.00".

## **9-17 Refer to ANSI/NIST-CSL 1-1993**

## **18 Type-10 facial & SMT image record**

Type-10 records shall contain facial and/or SMT binary image data and related ASCII information pertaining to the specific image contained in this record. It shall be used to exchange both grayscale and color image data. Image data contained in the Type-10 record may be uncompressed or compressed.

### **18.1 Fields for Type-10 logical record**

When there are one or more Type-10 logical records, entries shall be provided in ordered numbered fields. For each field of the Type-10 record, Table 10 summarizes the condition code as being mandatory(*M*) or optional(*O*); the field number, the field name, character type, size and occurrence limits, and the maximum size in bytes of the field. The two entries in the Field Size Per Occurrence include all character separators used in the field. The Maximum Byte Count includes the field number, the information, and all the character separators. Fields containing entries in the IMG column are only applicable to that image type. An entry of "FAC" applies to a mugshot or facial image, and an entry of "SMT" applies to scar, a mark, or a tattoo image. The following paragraphs describe the data

Table 10 Type-10 Logical Record Layout

IDENT	COND CODE	FIELD NUMBER	FIELD NAME	IMG	CHAR TYPE	FIELD SIZE PER OCCURRENCE		OCCUR COUNT		MAX BYTE COUNT
						MIN	MAX	MIN	MAX	
LEN	M	10.001	LOGICAL RECORD LENGTH		N	4	8	1	1	15
IDC	M	10.002	IMAGE DESIGNATION CHARACTER		N	2	5	1	1	12
IMT	M	10.003	IMAGE TYPE		A	5	7	1	1	14
SRC	M	10.004	SOURCE AGENCY / ORI		AN	10	21	1	1	28
PHD	M	10.005	PHOTO DATE		N	9	9	1	1	16
HLL	M	10.006	HORIZONTAL LINE LENGTH		N	4	5	1	1	12
VLL	M	10.007	VERTICAL LINE LENGTH		N	4	5	1	1	12
SLC	M	10.008	SCALE UNITS		N	2	2	1	1	9
HPS	M	10.009	HORIZONTAL PIXEL SCALE		N	3	5	1	1	12
VPS	M	10.010	VERTICAL PIXEL SCALE		N	3	5	1	1	12
CGA	M	10.011	COMPRESSION ALGORITHM		A	5	7	1	1	14
CSP	M	10.012	COLOR SPACE		A	4	5	1	1	12
RSV	-	10.013 10.019	RESERVED FOR FUTURE INCLUSION		--	--	--	--	--	--
POS	O	10.020	SUBJECT POSE	FAC	A	2	2	0	1	9
POA	O	10.021	POSE OFFSET ANGLE	FAC	N	2	5	0	1	12
PXS	O	10.022	PHOTO DESCRIPTION	FAC	A	4	21	0	9	196
RSV	-	10.023 10.039	RESERVED FOR FUTURE INCLUSION		--	--	--	--	--	---
SMT	M	10.040	NCIC DESIGNATION CODE	SMT	A	4	11	1	3	40
SMS	O	10.041	SCAR/MARK/TATTOO SIZE	SMT	N	4	6	0	1	13
SMD	O	10.042	SMT DESCRIPTORS	SMT	AN	16	51	0	9	466
COL	O	10.043	COLORS PRESENT	SMT	A	4	21	0	9	196
RSV	-	10.044 10.199	RESERVED FOR FUTURE INCLUSION		--	--	--	--	--	---
UDF	O	10.200 10.998	USER DEFINED FIELDS		--	--	--	--	--	---
DAT	M	10.999	IMAGE DATA		B	2	5,000,001	1	1	5,000,008

KEY FOR CHARACTER TYPE: N=NUMERIC; A=ALPHABETIC; AN=ALPHANUMERIC; B=BINARY

contained in each of the fields for the Type-10 logical record. Each field shall begin with a seven character ASCII identifier of the form "10.xxx:". The first two characters are the record type followed by a period. The next three characters are the appropriate field number followed by a colon. Descriptive ASCII information or the binary image data follows the seven character identifier.

### **18.1.1 Field 10.001: Logical Record Length (LEN)**

This mandatory ASCII field shall contain the total count of the number of bytes in the Type-10 logical record. Field *10.001* shall specify the length of the record including every character of every field contained in the record and the information separators. The *GS* character shall separate the length code of Field *10.001* from the next field.

### **18.1.2 Field 10.002: Image Designation Character (IDC)**

This mandatory one to four byte ASCII field shall be used to identify the facial or SMT image data contained in the record. This IDC shall match the IDC found in the file content field of the Type-1 record.

### **18.1.3 Field 10.003: Image Type (IMT)**

This mandatory ASCII field is used to indicate the type of image contained in this record. It shall contain "FACE", "SCAR", "MARK", or "TATTOO" to indicate a face, scar, mark or tattoo image.

The field may also contain "OTHER" to indicate a user-defined miscellaneous type image. This entry provides the ability to use the Type-10 record structure to exchange images not addressed by other record types in the standard. However, additional field numbers for ASCII descriptors must be

greater than 200. The content of these fields shall conform to the requirements set forth by the agency to whom the transmission is being sent.

### **18.1.4 Field 10.004: Source Agency / ORI (SRC)**

This mandatory ASCII field shall contain the identification of the administration or organization that originally captured the facial image contained in the record. Normally, the Originating Agency Identifier (ORI) of the agency that captured the image will be contained in this field. The size and data content of this field shall be defined by the user and be in accordance with the receiving agency.

### **18.1.5 Field 10.005: Photo Date (PHD)**

This mandatory ASCII field shall contain the date that the facial or SMT image contained in the record was captured. The date shall appear as eight digits in the format *CCYYMMDD*. The *CCYY* characters shall represent the year the image was captured; the *MM* characters shall be the tens and units values of the month; and the *DD* characters shall be the tens and units values of the day in the month. For example, *19960229* represents February 29, 1996. The complete date must be a legitimate date and shall not exceed the current date.

### **18.1.6 Field 10.006: Horizontal Line Length (HLL)**

This mandatory ASCII field shall contain the number of pixels contained on a single horizontal line of the transmitted image.

### **18.1.7 Field 10.007: Vertical Line Length (VLL)**

This mandatory ASCII field shall contain the number of horizontal lines contained in the transmitted image.

### 18.1.8 Field 10.008: Scale Units (SLC)

This mandatory ASCII field shall specify the units used to describe the image sampling frequency (pixel density). A "1" in this field indicates pixels per inch, or a "2" indicates pixels per centimeter. A "0" in this field indicates no scale is given. For this case, the quotient of HPS/VPS gives the pixel aspect ratio.

### 18.1.9 Field 10.009: Horizontal Pixel Scale (HPS)

This mandatory ASCII field shall specify the pixel density used in the horizontal direction providing the SLC contains a "1" or a "2". Otherwise, it indicates the horizontal component of the pixel aspect ratio.

### 18.1.10 Field 10.010: Vertical Pixel Scale (VPS)

This mandatory ASCII field shall specify the pixel density used in the vertical direction providing the SLC contains a "1" or a "2". Otherwise, it indicates the vertical component of the pixel aspect ratio.

### 18.1.11 Field 10.011: Compression Algorithm (CGA)

This mandatory ASCII field shall specify the algorithm used to compress the color or grayscale image. An entry of "NONE" in this field indicates that the data contained in this record is uncompressed. For those images that are to be compressed, the preferred method for the compression of facial and SMT images is specified by the baseline mode of the JPEG algorithm formatted in accordance with the JPEG File Interchange Format, Version 1.02 (JFIF).<sup>4</sup> An entry of "JPEGB" indicates that the scanned or

---

<sup>4</sup>Developed by C-Cube Microsystems, 1778 McCarthy Blvd., Milpitas, CA 95035.

captured image was compressed using baseline JPEG. An entry of "JPEGL" indicates that the lossless mode of the JPEG algorithm was used to compress the image. If the image is captured in grayscale, then only the luminescence component will be compressed and transmitted. The FBI will maintain a registry of additional compression techniques and corresponding codes that may be used as they become available.

### 18.1.12 Field 10.012: Colorspace (CSP)

This mandatory ASCII field shall contain the color space used to exchange the image. For compressed images, the preferred colorspace using baseline JPEG and JFIF is YCbCr<sup>5</sup> to be coded as "YCC". An entry of "GRAY" shall be used for all grayscale images. This field shall contain "RGB" for uncompressed color images containing non-interleaved red, green, and blue pixels in that order. All other colorspaces are undefined.

### 18.1.13 Field 10.013-.019: Reserved for Future Definition (RSV)

These fields are reserved for inclusion in future revisions of this standard. None of these fields are to be used at this revision level. If any of these fields are present, they are to be ignored.

### 18.1.14 Field 10.020: Subject Pose (POS)

This optional field is to be used for the exchange of facial image data. When included, this field shall contain a one ASCII character code selected from Table-11 to describe the pose of the subject. For the angled pose entry "A", field 10.021 shall contain the offset angle from the full face orientation.

---

<sup>5</sup>Annex F contains the information necessary to perform conversions between 24-bit RGB pixels and the YCbCr color space.

**Table 11 - Subject Pose**

POSE DESCRIPTION	POSE CODE
Full Face Frontal	F
Right Profile (90 degree)	R
Left Profile (90 degree)	L
Angled Pose	A

### 18.1.15 Field 10.021: Pose Offset Angle (POA)

This field shall only be used for the exchange of facial image data if Field 10.020 (POS) contains an "A" to indicate an angled pose of the subject. This field should be omitted for a full face or a profile. This ASCII field specifies the pose position of the subject at any possible orientation within a circle. Its value shall be to a nearest degree.

The offset angle shall be measured from the full-face pose position and have a range of values from -180 degrees to +180 degrees. A positive angle is used to express the angular offset as the subject rotates from a full-face pose to their right (approaching a left profile). A negative angle is used to express the angular offset as the subject rotates from a full-face pose to their left (approaching a right profile). If the entry in the POS field is an "F", "L", or "R", the contents of this field are ignored.

### 18.1.16 Field 10.022: Photo Description (PXS)

This optional ASCII field shall be used for the exchange of facial image data. When present, it shall describe special attributes of the captured facial image. Attributes associated with the facial image may be selected from Table 12 and entered in this field.

**Table 12 - Photo Descriptors**

FACIAL IMAGE ATTRIBUTE	ATTRIBUTE CODE
Subject Wearing Glasses	GLASSES
Subject Wearing Hat	HAT
Subject Wearing Scarf	SCARF
Physical Characteristics	PHYSICAL
Other Characteristics	OTHER

Physical characteristics, such as "FRECKLES" may be entered as a subfield consisting of two information items. The first is "PHYSICAL" followed by the *US* separator, followed by the characteristic as listed in Part 4 Section 13 of the NCIC Code Manual (Third Edition; July 1984). The "OTHER" category is used to enter unlisted or miscellaneous attributes of the facial image. This information shall be entered as a two information item subfield. The first is "OTHER" followed by the *US* separator, followed by the unformatted text used to describe the attribute. Multiple attributes and subfields may be listed but must be separated by the *RS* character.

### 18.1.17 Field 10.023-.039: Reserved for Future Definition (RSV)

These fields are reserved for inclusion in future revisions of this standard. None of these fields are to be used at this revision level. If any of these fields are present, they are to be ignored.

### 18.1.18 Field 10.040: NCIC Designation Code (SMT)

This field is mandatory for a Type-10 record containing SMT image data. It is used to identify a general location of the captured scar, mark, or tattoo image. The contents of this field will be an entry chosen from Part 4 Section 13 of the NCIC Code Manual (Third Edition; July 1984). The captured image can encompass an area larger than that

specified by a single NCIC body part code for the particular image type. This situation can be accommodated by listing multiple NCIC codes separated by the RS separator character. In this case the primary code is listed first.

For the "marks" category, the NCIC manual lists the common locations for needle track marks. The body location codes listed for scars shall be used for other body part locations or other types of marks not listed in the NCIC Code Manual.

**18.1.19 Field 10.041: SMT Size (SMS)**

This optional field shall contain the dimensions of the scar, mark or tattoo. It shall consist of two information items. The height shall be the first information item followed by the US separator character followed by the width. Each dimension shall be entered to the nearest centimeter.

**18.1.20 Field 10.042: SMT Descriptors (SMD)**

This optional field is used to describe the SMT image. It shall consist of one or more subfields. Each subfield shall contain three or four information items that provide progressively detailed information describing the total image or a portion of the image.

The first information item of each subfield shall identify the source of the SMT. This item will contain "TATTOO" for the creation of a common tattoo or indelible image resulting from the pricking of the skin with a coloring matter; "CHEMICAL" if the SMT was created by the use of chemicals to burn the image into the skin; or "BRANDED" if the image was burned into the skin using a branding iron or other form of heat. The second information item shall be the general class code of tattoo chosen from Table 13. For each general class of tattoo, there are several defined

subclasses. The third information item of the subfield shall be the appropriate subclass code selected from Tables 14a - 14h which lists the various subclasses of tattoos for each of the general classes. The final and optional information item in this subfield shall be a free-form ASCII text string that provides additional qualifiers to describe the image or portion of the image. For example, to fully describe a tattoo, there may be a class description of "ANIMAL", with a subclass description of "DOG", and qualified by "golden retriever with an overbite". The information items will be separated by the US separator character.

**Table 13 Tattoo Classes**

CLASS DESCRIPTION	CLASS CODE
Human Forms and Features	HUMAN
Animals and Animal Features	ANIMAL
Plants	PLANT
Flags	FLAG
Objects	OBJECT
Abstractions	ABSTRACT
Insignias & Symbols	SYMBOL
Other Images	OTHER

An SMT image consisting of several parts or sub-images shall use multiple subfields, separated by the RS separator, to fully describe the various parts or features found in the total image. The first subfield shall describe the most predominant feature or sub-image contained in the SMT. Subsequent subfields shall describe additional portions of the image that are not part of the main or central focal point of the image. For example, a tattoo consisting of a man with a snake on the arm being followed by a dog may contain three subfields - one describing the man, a second describing the snake, and a third describing the dog.

**Table 14a Human Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
Male Face	MFACE
Female Face	FFACE
Abstract Face	ABFACE
Male Body	MBODY
Female Body	FBODY
Abstract Body	ABBODY
Roles (Knight, Witch, man, etc.)	ROLES
Sports Figures (Football Player, Skier, etc.)	SPORT
Male Body Parts	MBPART
Female Body Parts	FBPART
Abstract Body Parts	ABBPART
Skulls	SKULL
Miscellaneous Human Forms	MHUMAN

**Table 14b Animal Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
Cats & Cat Heads	CAT
Dogs & Dog Heads	DOG
Other Domestic Animals	DOMESTIC
Vicious Animals (Lions, Tigers, Wolves, etc.)	VICIOUS
Horses (Donkeys, Mules, etc.)	HORSE
Other Wild Animals	WILD
Snakes	SNAKE
Dragons	DRAGON
Birds (Cardinal, Hawk, etc.)	BIRD
Spiders, Bugs, and Insects	INSECT
Abstract Animals	ABSTRACT
Animal Parts	PARTS
Miscellaneous Animal Forms	MANIMAL

**Table 14c Plant Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
Narcotics	NARCOTICS
Red Flowers	REDFL
Blue Flowers	BLUEFL
Yellow Flowers	YELFL
Drawings of Flowers	DRAW
Rose	ROSE
Tulip	TULIP
Lily	LILY
Miscellaneous Plants, Flowers, Vegetables	MPLANT

**Table 14d Flags Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
American Flag	USA
State Flag	STATE
Nazi Flag	NAZI
Confederate Flag	CONFED
British Flag	BRIT
Miscellaneous Flags	MFLAG

**Table 14e Objects Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
Fire	FIRE
Weapons (Guns, Arrows, etc.)	WEAP
Airplanes	PLANE
Boats, Ships, and Other Vessels	VESSEL
Trains	TRAIN
Cars, Trucks, and Vehicles	VEHICLE
Mythical (Unicorns, etc.)	MYTH
Sporting Objects (Football, Ski, Hurdles, etc.)	SPORT
Water & Nature Scenes (Rivers, Sky, Trees, etc.)	NATURE
Miscellaneous Objects	MOBJECTS

**Table 14f Abstract Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
Figure(s)	FIGURE
Sleeve	SLEEVE
Bracelet	BRACE
Anklet	ANKLET
Necklace	NECKLC
Shirt	SHIRT
Body Band	BODBND
Head Band	HEDBND
Miscellaneous Abstract	MABSTRACT

**Table 14g Symbols Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
National Symbols	NATION
Political Symbols	POLITIC
Military Symbols	MILITARY
Fraternal Symbols	FRATERNAL
Professional Symbols	PROFESS
Gang Symbols	GANG
Miscellaneous Symbols	MSYMBOLS

**Table 14h Other Tattoo Subclasses**

SUBCLASS	SUBCLASS CODE
Wording (Mom, Dad, Mary, etc.)	WORDING
Freeform Drawings	FREEFRM
Miscellaneous Images	MISC

**18.1.21 Field 10.043: Color (COL)**

This optional field shall contain one subfield corresponding to each subfield contained in Field 10.042. Each subfield shall contain one or more information items that list the color(s) of the tattoo or part of the tattoo. For each subfield, the first information item in the subfield shall

be the predominant color chosen from Table 15. Additional colors for the subfield shall be entered as information items in the subfield separated by the *US* separator character.

**18.1.22 Field 10.044-199: Reserved for Future Definition (RSV)**

These fields are reserved for inclusion in future revisions of this standard. None of these fields are to be used at this revision level. If any of these fields are present, they are to be ignored.

**Table 15 Color Codes**

Color Description	Color Code
Black	BLACK
Brown	BROWN
Gray	GRAY
Blue	BLUE
Green	GREEN
Orange	ORANGE
Purple	PURPLE
Red	RED
Yellow	YELLOW
White	WHITE
Multi-colored	MULTI
Outlined	OUTLINE

### 18.1.23 Field 10.200-998: User Defined Fields (UDF)

These fields are user-definable fields. Their size and content shall be defined by the user and be in accordance with the receiving agency. If present they shall contain ASCII textual information.

### 18.1.24 Field 10.999: Image Data (DAT)

This field shall contain all of the grayscale or color data from a face, scar, mark, tattoo, or other image. It shall begin with the ASCII identifier "10.999:", and be followed by image data in a binary representation.

Each pixel of uncompressed grayscale data shall be quantized to eight bits (256 gray levels) contained in a single byte.

Uncompressed color image data shall be expressed as 24 bit RGB pixels. The first byte shall contain the eight bits for the red component of the pixel, the second byte shall contain the eight bits for the green component of the pixel, and the third byte shall contain the last eight bits for the blue component of the pixel. If compression is used, the pixel data shall be compressed in accordance with the compression technique specified in the GCA field. If the JPEG algorithm is used to compress the data, this field shall be encoded using the JFIF format specification.

## 18.2 End of Type-10 Logical Record

For the sake of consistency, immediately following the last byte of data from field 10.999 an *FS* separator shall be used to separate it from the next logical record. This separator must be included in the length field of the Type-10 record.

## 18.3 Additional Facial & SMT Image Records

Additional Type-10 records may be included in the logical file. For each additional facial image, a complete Type-10 logical record together with the *FS* separator is required.

*[Faint, illegible table with multiple rows and columns]*

## Annex E

### JPEG File Interchange Format

#### Version 1.02

September 1, 1992

Eric Hamilton  
C-Cube Microsystems  
1778 McCarthy Blvd.  
Milpitas, CA 95035

+1 408 944-6300

Fax: +1 408 944-6314

E-mail: [eric@c3.pla.ca.us](mailto:eric@c3.pla.ca.us)

# JPEG File Interchange Format

Version 1.02

## Why a File Interchange Format

JPEG File Interchange Format (JFIF) is a minimal file format which enables JPEG bitstreams to be exchanged between a wide variety of platforms and applications. This minimal format does not include any of the advanced features found in the TIFF JPEG specification or any application specific file format. The only purpose of this simplified format is to allow the exchange of JPEG compressed images.

## JPEG File Interchange Format features

- Uses JPEG compression
- Uses JPBG interchange format compressed image representation
- PC or Mac or UNIX workstation compatible
- Standard color space: one or three components. For three components YCbCr (CCIR 601-256 levels)
- APP0 marker used to specify Units, X pixel density, Y pixel density, thumbnail
- APP0 marker also used to specify JFIF extensions
- APP0 mater also used to specify application-specific information

### *JPEG Compression*

Although any JPEG process is supported by the syntax of the JFIF it is strongly recommended that the JPEG baseline process be used for the purposes of file interchange. This ensures maximum compatibility with all applications supporting JPEG. JFIF conforms to the JPEG Draft International Standard (ISO DIS 10918-1).

The JFIF is entirely compatible with the standard JPEG interchange format; the only additional requirement is the mandatory presence of the APP0 marker right after the SOI marker. Note that the JPEG interchange format requires (as does JFIF) all table specifications used in the encoding process be coded in the bitstream prior to their use.

### *Compatible across Platforms*

The JFIF is compatible across platforms: for example, it can use any resource forks supported by the Macintosh and by PCs or workstations, but not just one platform.

### *Standard color Space*

The color space to be used is YCbCr as defined by CCIR 601(256 levels). The RGB components calculated by linear conversion from YCbCr shall not be gamma corrected (gamma = 1.0). If only one component is used, that component shall be Y.

*APP0 marker is used to identify JPEG FIF*

The APP0 marker is used to identify a JPEG FIF file.

The JPEG FIF APP0 marker is mandatory right after the SOI marker.

The JFIF APP0 marker is identified by a zero terminated string: "JFIF".

The APP0 can be used for any other purpose by the application provided it can be distinguished from the JFIF APP0.

The JFIF APP0 marker provides information which is missing from the JPEG stream: version number, X and Y pixel density (dots per inch or dots per cm), pixel aspect ratio (derived from X and Y pixel density), thumbnail.

*APP0 marker used to specify JFIF extensions*

Additional APP0 marker segment(s) can optionally be used to specify JFIF extensions. If used, these segments must immediately follow the JFIF APP0 marker. Decoders should skip any unsupported JFIF extension segments and continue decoding.

The JFIF extension APP0 marker is identified by a zero terminated string: "JFXX". The JFIF extension APP0 marker segment contains a 1-byte code which identifies the extension. This version, version 1.02, has only one extension defined: an extension for defining thumbnails stored in formats other than 24-bit RGB.

*APP0 marker used for application-specific information*

Additional APP0 marker segments can be used to hold application-specific information which does not affect the decodability or displayability of the JFIF file. Application-specific APP0 marker segments must appear after the JFIF APP0 and any JFXX APP0 segments. Decoders should skip any unrecognized application-specific APP0 segments.

Application-specific APP0 marker segments are identified by a zero terminated string which identifies the application (not "JFIF" or "JFXX"). This string should be an organization name or company trademark. Generic strings such as dog, cat, tree, etc. should not be used.

**Conversion to and from RGB**

Y, Cb, and Cr are converted from R, G, and B as defined in CCIR Recommendation 601 but are normalized so as to occupy the full 256 levels of an 8-bit binary encoding. More precisely:

$$\begin{aligned} Y &= 256 * E'_y \\ Cb &= 256 * [ E'_{Cb} ] + 128 \\ Cr &= 256 * [ E'_{Cr} ] + 128 \end{aligned}$$

where the  $E'_y$ ,  $E'_{Cb}$  and  $E'_{Cr}$  are defined as in CCIR 601. Since values of  $E'_y$  have a range

of 0 to 1.0 and those for  $E'_{Cb}$  and  $E'_{Cr}$  have a range of -0.5 to +0.5, Y, Cb, and Cr must be clamped to 255 when they are maximum value.

#### *RGB to YCbCr Conversion*

YCbCr (256 levels) can be computed directly from 8-bit RGB as follows:

$$\begin{aligned} Y &= 0.299 R + 0.587G + 0.114B \\ Cb &= -0.1687 R - 0.3313 G + 0.5 B + 128 \\ Cr &= 0.5R - 0.4187 G - 0.0813 B + 128 \end{aligned}$$

NOTE - Not all image file formats store image samples in the order  $R_0, G_0, B_0, \dots, R_n, G_n, B_n$ . Be sure to verify the sample order before converting an RGB file to JFIF

#### *YCbCr to RGB Conversion*

RGB can be computed directly from YCbCr (256 levels) as follows:

$$\begin{aligned} R &= Y + 1.402 (Cr - 128) \\ G &= Y - 0.34414 (Cb - 128) - 0.71414 (Cr - 128) \\ B &= Y + 1.772 (Cb - 128) \end{aligned}$$

### **Image Orientation**

In JFIF files, the image orientation is always top-down. This means that the first image samples encoded in a JFIF file are located in the upper left hand corner of the image and encoding proceeds from left to right and top to bottom. Top-down orientation is used for both the full resolution image and the thumbnail image.

The process of converting an image file having bottom-up orientation to JFIF must include inverting the order of all image lines before JPEG encoding.

### **Spatial Relationship of Components**

Specification of the spatial positioning of pixel samples within components relative to the samples of other components is necessary for proper image post processing and accurate image presentation. In JFIF files, the position of the pixels in subsampled components are defined with respect to the highest resolution component. Since components must be sampled orthogonally (along rows and columns), the spatial position of the samples in a given subsampled component may be determined by specifying the horizontal and vertical offsets of the first sample, i.e. the sample in the upper left corner, with respect to the highest resolution component.

The horizontal and vertical offsets of the first sample in a subsampled component,  $Xoffset_i[0,0]$  and  $Yoffset_i[0,0]$ , are defined to be:

$$\begin{aligned} Xoffset_i[0,0] &= ((Nsamples_{ref} / Nsamples_i) / 2) - 0.5 \\ Yoffset_i[0,0] &= ((Nlines_{ref} / Nlines_i) / 2) - 0.5 \end{aligned}$$

where


$N_{\text{samples}_{\text{ref}}}$  is the number of samples per line in the largest component;  
 $N_{\text{samples}_i}$  is the number of samples per line in the  $i$ th component;  
 $N_{\text{lines}_{\text{ref}}}$  is the number of lines in the largest component;  
 $N_{\text{lines}_i}$  is the number of lines in the  $i$ th component.

Proper subsampling of components incorporates an anti-aliasing filter which reduces the spectral bandwidth of the full resolution components. Subsampling can easily be accomplished using a symmetrical digital filter with an even number of taps (coefficients). A commonly used filter for 2:1 subsampling utilizes two taps (1/2,1/2).

As an example, consider a 3 component image which is comprised of components having the following dimensions:

Component 1: 256 samples, 288 lines  
 Component 2: 128 samples, 144 lines  
 Component 3: 64 samples, 96 lines

In a JFIF file, centers of the samples are positioned as illustrated below:



NOTE - This definition is compatible with industry standards such as Postscript Level 2 and QuickTime. This definition is not compatible with the conventions used by CCIR Recommendation 601-I and other digital video formats. For these formats, pre-processing of the chrominance components is necessary prior to compression in order to ensure accurate reconstruction of the compressed image.

## JPEG File Interchange Format Specification

The syntax of a JFIF file conforms to the syntax for interchange format defined in Annex B of ISO DIS 10918-1. In addition, a JFIF file uses APP0 marker segments and constrains certain parameters in the frame header as defined below.

X'FF', SOI

X'FF', APP0, length, identifier, version, units, Xdensity, Ydensity, Xthumbnail, Ythumbnail, (RGB)<sub>n</sub>

length	(2 bytes)	Total APP0 field byte count, including the byte count value (2 bytes), but excluding the APP0 marker itself
identifier	(5 bytes)	= X'4A', X'46', X'49', X'46', X'00' This zero terminated string ("JFIF") uniquely identifies this APP0 marker. This string shall have zero parity (bit 7=0).
version	(2 bytes)	= X'0102' The most significant byte is used for major revisions, the least significant byte for minor revisions. Version 1.02 is the current released revision.
units	(1 byte)	Units for the X and Y densities units = 0: no units, X and Y specify the pixel units = 1: X and Y are dots per inch units = 2: X and Y are dots per cm
Xdensity	(2 bytes)	Horizontal pixel density
Ydensity	(2 bytes)	Vertical pixel density
Xthumbnail	(1 byte)	Thumbnail horizontal pixel count
Ythumbnail	(1 byte)	Thumbnail vertical pixel count
(RGB) <sub>n</sub>	(3n bytes)	Packed (24-bit) RGB values for the thumbnail pixels, n = Xthumbnail * Ythumbnail

[Optional JFIF extension APP0 marker segment(s) - see below]

·  
·  
·

X 'FF', SOF<sub>n</sub>, length, frame parameters

Number of components	Nf	= 1 or 3
1st component	C <sub>1</sub>	= 1 = Y component
2nd component	C <sub>2</sub>	= 2 = Cb component
3rd component	C <sub>3</sub>	= 3 = Cr component
	·	
	·	
	·	

X 'FF', EOI

**JFIF Extension APP0 Marker Segment**

Immediately following the JFIF APP0 marker segment may be a JFIF extension APP0 marker. This JFIF extension APP0 marker segment may only be present for JFIF versions 1.02 and above. The syntax of the JFIF extension APP0 marker segment is:

X 'FF', APP0, Length, identifier, extension code, extension data

length	(2 bytes)	Total APP0 field byte count, including the byte count value (2 bytes), but excluding the APP0 marker itself
identifier	(5 bytes)	= X '4A', X '46', X '58', X '58', X '00'  This zero terminated string ("JFXX") uniquely identifies this APP0 marker. This string shall have zero parity (bit 7 = 0).
extension_code	(1 byte)	= Code which identifies the extension. In this version, the following extensions are defined:  = X '10' Thumbnail coded using JPEG = X '11' Thumbnail stored using 1 byte/pixel = X '13' Thumbnail stored using 3 bytes/pixel
extension_data	(variable)	= The specification of the remainder of the JFIF extension APP0 marker segment varies with the extension. See below for a specification of extension_data for each extension.

**JFIF Extension: Thumbnail coded using JPEG**

This extension supports thumbnails compressed using JPEG. The compressed thumbnail immediately follows the extension-code (X '10') in the extension\_data field and the length of the compressed data must be included in the JFIF extension APP0 marker length field.

The syntax of the extension\_data field conforms to the syntax for interchange format defined in Annex B of ISO DIS 10918-1. However, no "JFIF" or "JFXX" marker segments shall be present. As in the full resolution image of the JFIF file, the syntax of extension\_data constrains parameters in the frame header as defined below:

X 'FF', SOI

•  
•

X'FF', SOF<sub>n</sub>, length, frame parameters

Number of components	Nf = 1 or 3
1st component	C <sub>1</sub> = 1 = Y component
2nd component	C <sub>2</sub> = 2 = Cb component
3rd component	C <sub>3</sub> = 3 = Cr component

•  
•

X 'FF', EOI

**JFIF Extension: Thumbnail stored using one byte per pixel**

This extension supports thumbnails stored using one byte per pixel and a color palette in the extension\_data field. The syntax of extension\_data is:

Xthumbnail	(1 byte)	Thumbnail horizontal pixel count
Ythumbnail	(1 byte)	Thumbnail vertical pixel count
palette	(768 bytes)	24-bit RGB pixel values for the color palette. The RGB values define the colors represented by each value of an 8-bit binary encoding (0 - 255).
(pixel) <sub>n</sub>	(n bytes)	8-bit values for the thumbnail pixels n = Xthumbnail * Ythumbnail

**JFIF Extension: Thumbnail stored using three bytes per pixel**

This extension supports thumbnails stored using three bytes per pixel in the extension\_data field. The syntax of extension\_data is:

Xthumbnail	(1 byte)	Thumbnail horizontal pixel count
Ythumbnail	(1 byte)	Thumbnail vertical pixel count
(RGB) <sub>n</sub>	(3n bytes)	Packed (24-bit) RGB values for the thumbnail pixels, n = Xthumbnail * Ythumbnail

**Useful tips**

- you can identify a JFIF file by looking for the following sequence: X'FF', SOI, X'FF', APP0, <2 bytes to be skipped>, "JFIF", X'00'.
- if you use APP0 elsewhere, be sure not to have the strings "JFIF" or "JFXX" right after the APP0 marker.
- if you do not want to include a thumbnail, just program Xthumbnail = Ythumbnail = 0.
- be sure to check the version number in the special APP0 field. In general, if the major version number of the JFIF file matches that supported by the decoder, the file will be decodable.
- if you only want to specify a pixel aspect ratio, put 0 for the units field in the special APP0 field. Xdensity and Ydensity can then be programmed for the desired aspect ratio. Xdensity = 1, Ydensity = 1 will program a 1:1 aspect ratio. Xdensity and Ydensity should always be non-zero.

## Annex F

### An Example of the Use of the Standard

This example contains a transaction information record (Type-1), a user-defined descriptive text record (Type-2), a facial image record (Type-10), and a tattoo image record (Type-10). The pose in the facial image was halfway between a full-face and right profile pose. A compression ratio of approximately 20:1 and 25:1 was used for the facial record and tattoo records respectively.

#### TYPE-1 RECORD

*LENGTH (LEN)	1.01:151 <sup>G</sup> <sub>S</sub>
*VERSION (VER)	1.02:0201 <sup>G</sup> <sub>S</sub>
*CONTENT (CNT)	1.03:1 <sup>U</sup> <sub>S</sub> 3 <sup>R</sup> <sub>S</sub> 02 <sup>U</sup> <sub>S</sub> 00 <sup>R</sup> <sub>S</sub> 10 <sup>U</sup> <sub>S</sub> 01 <sup>R</sup> <sub>S</sub> 10 <sup>U</sup> <sub>S</sub> 02 <sup>G</sup> <sub>S</sub>
*TYPE OF TRANSACTION (TOT)	1.04:XXX <sup>G</sup> <sub>S</sub>
*DATE (DAT)	1.05:19960229 <sup>G</sup> <sub>S</sub>
PRIORITY (PRY)	1.06:1 <sup>G</sup> <sub>S</sub>
*DESTINATION AGENCY IDENTIFIER (DAI)	1.07:DCFBWA6Z <sup>G</sup> <sub>S</sub>
*ORIGINATING AGENCY IDENTIFIER (ORI)	1.08:NY0303000SLAS01000 <sup>G</sup> <sub>S</sub>
*TRANSACTION CONTROL NUMBER (TCN)	1.09:234567AB <sup>G</sup> <sub>S</sub>
*NATIVE SCANNING RESOLUTION (NSR)	1.11:00.00 <sup>G</sup> <sub>S</sub>
*TRANSMITTING RESOLUTION	1.12:00.00 <sup>F</sup> <sub>S</sub>

#### TYPE-2 RECORD

*LENGTH (LEN)	2.01:356 <sup>G</sup> <sub>S</sub>
*IMAGE DESIGNATION CHARACTER (IDC)	2.02:00 <sup>G</sup> <sub>S</sub>
USER-DEFINED INFORMATION	(338 ASCII TEXT CHARACTERS) <sup>F</sup> <sub>S</sub>
*MANDATORY FIELDS	

TYPE-10 RECORD (FACIAL)1ST TYPE-10 RECORD --

*LENGTH (LEN)	10.001:14601 <sup>G</sup> <sub>S</sub>
*IMAGE DESIGNATION CHARACTER (IDC)	10.002:01 <sup>G</sup> <sub>S</sub>
*IMAGE TYPE (IMT)	10.003:FACE <sup>G</sup> <sub>S</sub>
*SOURCE AGENCY (SRC)	10.004:NY0303000SLAS01000 <sup>G</sup> <sub>S</sub>
*PHOTO DATE (PHD)	10.005:19960229 <sup>G</sup> <sub>S</sub>
*HORIZONTAL LINE LENGTH (HLL)	10.006:480 <sup>G</sup> <sub>S</sub>
*VERTICAL LINE LENGTH (VLL)	10.007:600 <sup>G</sup> <sub>S</sub>
*SCALE UNITS (SLC)	10.008:0 <sup>G</sup> <sub>S</sub>
*HORIZONTAL PIXEL SCALE (HPS)	10.009:1 <sup>G</sup> <sub>S</sub>
*VERTICAL PIXEL SCALE (VPS)	10.010:1 <sup>G</sup> <sub>S</sub>
*COMPRESSION ALGORITHM (CGA)	10.011:JPEGB <sup>G</sup> <sub>S</sub>
*COLORSPACE (CSP)	10.012:YCC <sup>G</sup> <sub>S</sub>
SUBJECT POSE (POS)	10.020:A <sup>G</sup> <sub>S</sub>
POSE OFFSET ANGLE (POA)	10.021:-45 <sup>G</sup> <sub>S</sub>
PHOTO DESCRIPTION (PXS)	10.022:HAT <sup>R</sup> <sub>S</sub> GLASSES <sup>G</sup> <sub>S</sub>
*IMAGE DATA (DAT)	10.999:
SOI & APP0 Marker Segment	X'FFD8', X'FFE0' X'0010' X'4A46494600', X'0102', X'00', X'0001', X'0001', X'00', X'00',
Compressed Image Data	(FACIAL DATA COMPRESSED @ 20:1 TO 14382 BYTES)
End Of Image Marker Code	X'FFD9' <sup>F</sup> <sub>S</sub>

TYPE-10 RECORD (TATTOO)2ND TYPE-10 RECORD --

*LENGTH (LEN)	10.001:11797 <sup>G</sup> <sub>S</sub>
*IMAGE DESIGNATION CHARACTER (IDC)	10.002:02 <sup>G</sup> <sub>S</sub>
*IMAGE TYPE (IMT)	10.003:TATTOO <sup>G</sup> <sub>S</sub>
*SOURCE AGENCY (SRC)	10.004:NY0303000SLAS01000 <sup>G</sup> <sub>S</sub>
*PHOTO DATE (PHD)	10.005:19960229 <sup>G</sup> <sub>S</sub>
*HORIZONTAL LINE LENGTH (HLL)	10.006:480 <sup>G</sup> <sub>S</sub>
*VERTICAL LINE LENGTH (VLL)	10.007:600 <sup>G</sup> <sub>S</sub>
*SCALE UNITS (SLC)	10.008:0 <sup>G</sup> <sub>S</sub>
*HORIZONTAL PIXEL SCALE (HPS)	10.009:1 <sup>G</sup> <sub>S</sub>
*VERTICAL PIXEL SCALE (VPS)	10.010:1 <sup>G</sup> <sub>S</sub>
*COMPRESSION ALGORITHM (CGA)	10.011:JPEGB <sup>G</sup> <sub>S</sub>
*COLORSPACE (CSP)	10.012:YCC <sup>G</sup> <sub>S</sub>
*NCIC DESIGNATION CODE (SMT)	10.040:TAT R ANKL <sup>G</sup> <sub>S</sub>
SCAR/MARK/TATTOO SIZE (SMS)	10.041:5 <sup>U</sup> <sub>S</sub> 10 <sup>G</sup> <sub>S</sub>
TATTOO DESCRIPTION (TAT)	10.042:TATTOO <sup>U</sup> <sub>S</sub> OBJECT <sup>U</sup> <sub>S</sub> NATURE <sup>U</sup> <sub>S</sub> SUNBURST <sup>R</sup> <sub>S</sub> TATTOO <sup>U</sup> <sub>S</sub> HUMAN <sup>U</sup> <sub>S</sub> ROLES <sup>U</sup> <sub>S</sub> KNIGHT <sup>G</sup> <sub>S</sub>
COLORS PRESENT (COL)	10.043:MULTI <sup>R</sup> <sub>S</sub> GRAY <sup>U</sup> <sub>S</sub> BLUE <sup>G</sup> <sub>S</sub>
*IMAGE DATA (DAT)	10.999:  SOI & APP0 Marker Segment X'FFD8', X'FFE0' X'0010' X'4A46494600', X'0102', X'00', X'0001', X'0001', X'00', X'00', Compressed Image Data (TATTOO DATA COMPRESSED @ 25:1 TO 11499 BYTES) End Of Image Marker Code X'FFD9' <sup>F</sup> <sub>S</sub>





